




SKYLUX

SKYLUX200W-G2

SAP CODE: 2002091




200W, 0-10V Dimming,
Wide voltage range,
Power switchable LED
High efficacy Highbay

A versatile, cost effective LED
Highbay for lighting large
industrial spaces



Photometric
Diagram



Unit: cd
- C0/180 114.1deg
- C90/270 115.7deg

KEY INFORMATION

Lumen Output	19000/22000/25000/30000lm
Input Power	130/150/170/200W
Dimming Options	0-10V Dimming
Trim Colour	BLACK
Warranty	5yr
IP Rating	IP65
IK Rating	IK08

PHOTOMETRIC

Efficacy	150lm/W
LED	SMD
CCT	5000K
CRI	80
Beam Angle	110°

ELECTRICAL

Driver	Integral
Supply Input	100-277V, 50/60Hz
Driver Output Voltage	200VDC
Power Factor	>0.9
LED Input Current (nominal)	700-1000mA
Useful life @Ta25° (L70)	50,000hr

CONSTRUCTION

Housing	Aluminium ADC12
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	N/A
Connection Type	1.5m Flex & Plug
Total Weight	4kg
Dimensions	Ø340 x 197mm
Operating Ambient Temp.	-35 to 50°C
Electrical Classification	Class 1