

### Product data sheet Characteristics

# LAD703B

## TeSys Deca thermal overload relays - remote electrical stop - 24 V DC/AC





| Main                               |                                |
|------------------------------------|--------------------------------|
| Range                              | TeSys                          |
| Product or component type          | Electrical remote stop         |
| Device short name                  | LAD                            |
| Accessory / separate part category | Electrical accessory           |
| Product compatibility              | LRD313LRD365<br>LR3D313LR3D365 |

LR3D01...D35

LRD01...35

LR9G [Uc] control circuit 24 V AC 50/60 Hz 24 V DC voltage

#### Complementary

| Maximum inrush power in VA | 100 VA  |  |
|----------------------------|---------|--|
| Inrush power in W          | 0100 W  |  |
| Net weight                 | 0.09 kg |  |

### **Packing Units**

| Unit Type of Package 1       | PCE      |
|------------------------------|----------|
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 110.0 g  |
| Package 1 Height             | 4.9 cm   |
| Package 1 width              | 4.9 cm   |
| Package 1 Length             | 5.3 cm   |
| Unit Type of Package 2       | S01      |
| Number of Units in Package 2 | 32       |
| Package 2 Weight             | 3.705 kg |
| Package 2 Height             | 15.0 cm  |
| Package 2 width              | 15.0 cm  |
| Package 2 Length             | 40.0 cm  |
|                              |          |

#### Offer Sustainability

| Sustainable offer status   | Green Premium product   |
|----------------------------|---|
| REACh Regulation           | ☑ REACh Declaration   |
| EU RoHS Directive          | Compliant EEU RoHS Declaration  |
| Mercury free               | Yes   |
| RoHS exemption information | ₫Yes  |
| China RoHS Regulation      | ☑ China RoHS Declaration  |
| Environmental Disclosure   | <sup>☑</sup> Product Environmental Profile  |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
|                            |   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Warranty 18 months